AMENDMENTS TO THE CLAIMS

1 (Currently amended) A nail clipper comprising

a top elongated member having a top surface, a bottom surface, a pair of side surfaces connecting the top and bottom surfaces, and distal and proximal ends;

a bottom elongated member having a top surface, a bottom surface, a pair of side surfaces connecting the top and bottom surfaces, and distal and proximal ends;

the top and bottom clongated members being interconnected by a post extending from the top surface of the bottom elongated member adjacent the proximal end thereof and adjacent to and outwardly of a side surface of the top elongated member to a point above the top surface of the top elongated member;

each of the proximal ends of the top and bottom members having a cutting edge disposed in opposing nail clipping relationship;

a lever coupled to the post above the top surface of the top member, the lever <u>disposed and</u> adapted to cause movement of the cutting edges between a cutting position and non-cutting position; and

a bumper disposed on the bottom surface of the bottom member, the bumper having an edge disposed distant from the proximal end of the bottom member,

wherein the lever lacks a hole through which [[a]] the post extends.

2 - 4 (Canceled).

5 (original). A nail clipper according to claim 1, wherein the bumper extends from about the proximal end to said edge and has a generally triangular shape whose apex is distant from the bottom elongated member.

6 (Previously presented) A nail clipper according to claim 17, wherein said lever includes a thumb accepting depression.

7 (Previously presented). A nail clipper according to claim 6, wherein the cutting edges are disposed at an angle to a central longitudinal axis of the top and bottom elongated members.

8 (Previously presented). A nail clipper according to claim 1, wherein the cutting edges are disposed at an angle to a central longitudinal axis of the top and bottom elongated members.

9 - 15 (Canceled)

16 (Previously presented) A nail clipper according to claim 1, wherein the distal ends of the top and bottom elongated members are interconnected.

17 (Previously presented) A nail clipper according to claim 1, wherein the distal ends of the top and bottom elongated members are not interconnected.

18 - 19 (Canceled)

20 (Previously presented). A nail clipper according to claim 22, wherein the bumper extends from about the distal end to said edge and has a generally triangular shape whose apex is distant from the bottom elongated member.

21. (Canceled)

22 (Currently amended) A nail clipper comprising

a top elongated members having a top surface, a bottom surface, a pair of side surfaces, and distal and proximal ends;

a bottom elongated member having a top surface, a bottom surface, a pair of side surfaces connecting the top and bottom surfaces, and distal and proximal ends;

the distal ends of the top and bottom elongated members not being interconnected:

the top and bottom elongated members being interconnected by a post extending from the top surface of the bottom elongated member adjacent the proximal end thereof, abutting and interconnected to a side surface of the top elongated member to a point above the top surface of the top elongated member;

each of the proximal ends of the top and bottom members having a cutting edge disposed in opposing nail clipping relationship, wherein the cutting edges are disposed at an angle to the central longitudinal axis of the top and bottom elongated members;

a lever coupled to the post above the top surface of the top member, the lever disposed and adapted to cause movement of the cutting edges between a cutting position and non-cutting position, the lever including a thumb accepting depression; and

a bumper disposed on the bottom surface of the bottom member, the bumper having an edge disposed distant from the proximal end of the bottom member, wherein the lever lacks a hole through which [[a]] the post extends.